TOSHIBA
Toshiba Pocket PC e350 Series
Featured Products:

e350: Intel® PXA255 at 300MHz/3.5", 240x320 TFT/16MB(ROM)-64MB(RAM)/SD/MS Pocket PC 2003

e355: Intel® PXA255 at 300MHz/3.5",240x320 TFT/16MB(ROM)-64MB(RAM)/SD/MS Pocket PC 2003/ArcSoft PhotoBase™

Part Numbers

PD350U-00002R

PD350U-00002RR

Product Highlights

- Value-priced and powered by the Intel® PXA255 processor with Intel XScale™ technology at 300MHz, the Toshiba Pocket PC e350/e355 Series is designed for both general productivity applications (PIM/calendar functionality). In addition, it can be used for vertical applications such as point of care in the healthcare industry, quality assurance in manufacturing and clinical trials in the pharmaceutical industry.
- Easy to use, the Toshiba Pocket PC e350/e355 Series features the new Microsoft® Pocket PC 2003 operating system delivering enhanced schedule/calendar capabilities and data backup synchronization.
- One of the thinnest PDA devices on the market, the Toshiba Pocket PC e350/e355 Series weighs a mere 5.1 ounces and is packaged in an attractive premium graphite casing.
- Perfect for viewing files and images indoor or outdoors, the Toshiba Pocket PC e350/e355 Series features a bright 3.5" transreflective display offering 64K colors and a 240x320 resolution. The bright display will work where lesser models can't, providing a competitive advantage and greater return on investment.
- Play audio and video files, organize and view your favorite pictures, all with the Toshiba Pocket PC e350/e355 Series' incredible expansion capabilities, including an integrated Secure Digital (SD) media slot for additional memory or wireless connectivity (via the optional Bluetooth™ SD card) and USB-host functionality*** allowing the user to plug the device into a full-size keyboard.

System Characteristics

Processor
- Intel® PXA255 processor at 300MHz

Memory
- Main memory: 64MB SDRAM; 3.3V
- Program memory: 16MB CMOS Flash ROM

Display
- 3.5" TFT reflective color display; 240 x 320 (portrait) resolution (16 bit)
- Backlight fluorescent lamp
- 65,536 (64K) colors; 5 step Brightness control (by Software)

Input Devices
- **Touch Panel:** Analog resistance sensitive system touch panel
- **Controls/Buttons:** 5-way navigation button; 4 application keys-Calendar, Contacts, Task, Menu; 3 function navigator (Toshiba Scroller) for Up, Down and Action; Reset switch; Voice record button; Power on/off button; Battery on/off switch, Stylus pen

Expandability
- 1 SDIO (Secure Digital) card slot (3.3V)

Ports
- Universal Serial Bus port – **(Client, Host***)**
- IrDA Infrared port (115kbps)
- DC-in
- Cradle connector port (26 pins)
- Stereo headphone jack

Physical Description
- Dimensions (LxWxH): 4.9" x 3.1" x 0.4"
- Weight: 5.2oz (w/Stylus & battery)
- LED Indicators: One 2 color (Green, Orange) LED for Power Indication:
    1. Green: Full Charge (while power source is AC adaptor)
    2. Orange: Charging (while power source is AC adaptor)
    3. Orange Flash: Alarm
    4. Yellow (Green and Orange): Out of Temperature
    5. Off: Power on/off

Sound
- AC-97 Codec Chip; WM9705 Sound Chip
- 16-bit stereo; 44.1KHz Sample Rate

- Full Duplex Record and Playback
- Software Volume Control (by software)
- Built-in Microphone and Built-in Speaker
- Stereo Headphone jack

Power Supply
- **AC Adapter:** 5V/2A DC output; 100-240V input voltage, 50/60Hz frequency
- **Battery Pack:** Rechargeable Advanced Lithium-Ion battery; 3.7V / 1000 mAh
- Battery Saver: Stand by, Display Auto Off
- Recharge time (Main battery on/off): 4h/4h

Operating System
- **Microsoft® Pocket PC 2003**

Additional Software
- Pocket Word
- Pocket Excel
- Pocket Outlook®
- Pocket Internet Explorer
- Microsoft® Windows® Media™ Player 9 for Pocket PC
- File Explorer
- MSN® Messenger
- Microsoft® Active Sync® 3.7
- Microsoft® Outlook®
- ArcSoft PhotoBase™ **(e355 only)**

Warranty
- 1 year parts, labor and battery
- 90-day limited warranty on operating system and applications

Environmental Specifications
- **Temperature:** Operating: 0° to 40°C (32° to 104°F); Non-operating: -20° to 65°C (-4° to 149°F)
- **Relative Humidity:** Operating: 30% to 80%
- **Altitude (relative to sea level):**
    Operating: 10,000ft; Altitude change rate: 2000ft/min.
    Non-operating: 40,000ft; Altitude change rate: 2000ft/min.

Accessories

PA1309U-1PPS	USB Power Sync Cable
PA3243U-1ETC	USB Host Cable
PA3183U-1ACA	10W AC Adapter
PA3186U-1DST	USB Cradle
PA3182U-1ETC	Stylus Pen (3-pack)
PA3271U-1BTM	Toshiba SD Bluetooth II
SD-M3203B3	32MB SD (Secure Digital) Card
SD-M6403B3	64MB SD (Secure Digital) Card
SD-M1283B3	128MB SD (Secure Digital) Card
SD-M2564B3	256MB SD (Secure Digital) Card
PA1301U-2PCS	Leather Holster Case
PA1302U-1PMS	Screen Overlays
PA1307U-1PCS	Universal Case
NW780U	Targus-Noteworthy Click N Type (Thumb Input Device)
F8A1500	Belkin Foldable Keyboard

Product/Part Numbers/UPC

Pocket PC e350	PD350U-00002R
Pocket PC e355	PD350U-00002RR

*** requires USB Host Cable (PA3243U-1ETC)